

LED Street Lights

Light the path to the future with LED Street Lights. This state of the art LED Technology provides uniform Brightness and Illumination. Featuring V-TAC's eco-friendly street lights.

Product Features

- Perfect replacement for traditional lights
- Saves 80% electricity cost, better efficiency and Longer life span
- Dedicated ip65 sealed optical cavities
- Optically optimized glass lenses
- Uniformity in light distribution - maximizes efficiency
- Fully operational in extreme weather up to -25° celsius
- Low maintenance & low power consumption
- Reduced co² emissions

Applications

Out door applications like streets, projects, cross roads, tunnels, car parks, industrial facilities etc.

Streetlight-Photo Cell Sensor

30w VT-15031ST



SKU: 5489 - 4000K Day White 3800157623483
SKU: 5490 - 6400K White 3800157623490



PHOTOCELL SENSOR
Auto Turns On At Night
Auto Turns Off At Day Time



IP65 RATING



Sensor Compatible:	Yes
Voltage/Frequency:	AC:190-240V,50/60Hz
Luminous Flux:	2400lm
LED Type:	SMD
IP Rating:	IP65
Dimension:	175x373x52mm

CRI:	>70
PF:	>0.9
Beam Angle:	100°
Body Type:	Die Cast Aluminium
Box Qty:	1 Pcs

Streetlight-Photo Cell Sensor

50w VT-15052ST



SKU: 5493 - 4000K Day White 3800157623520
SKU: 5494 - 6400K White 3800157623537



PHOTOCELL SENSOR
Auto Turns On At Night
Auto Turns Off At Day Time



IP65 RATING



Sensor Compatible:	Yes
Voltage/Frequency:	AC:190-240V,50/60Hz
Luminous Flux:	4000lm
LED Type:	SMD
IP Rating:	IP65
Dimension:	213.5x460x62mm

CRI:	>70
PF:	>0.9
Beam Angle:	100°
Body Type:	Die Cast Aluminium
Box Qty:	1 Pcs

50W Solar Panel With Streetlight

VT-ST200

SKU: 5502 - 4000K Day White 3800157652339



Battery:	Li-ion 6.4V/27.5AH Battery
Charging Time:	4-6 hrs Sunlight Charging
Working Time-Volt:	12-15Hours
age/Frequency:	DC:3.2V
Luminous Flux:	4000lm
LED Type:	SMD

IP Rating:	IP65
CRI:	>70
Beam Angle:	120°
Body Type:	Aluminium
Box Qty:	1 Pcs



Solar Streetlight-Black Cover

15w VT-ST15

SKU: 8549 - 4000K Day White 3800157639200
SKU: 8548 - 6000K White 3800157639217

Battery:	7.4V Lithium Battery,10800mAh
Lumens:	1600lm
No. of LED:	40
Detecting Angle:	120°
Sensing Range:	3-8M



Charging Time:	6-7 Hours
IP Rating:	IP65
Material:	ABS+PC
Dimension:	413x232x58mm
Working Time:	2-36 Hours
Box Qty:	10 Pcs



Streetlight

50W VT-15050ST

SKU: 9757 - 6000K White



Sensor Compatible:	Yes
Voltage/Frequency:	AC:85-265V,50/60Hz
Luminous Flux:	4250lm
LED Type:	SMD
IP Rating:	IP65
Dimension:	495x210x55mm



CRI:	>70
PF:	>0.9
Beam Angle:	100°
Body Type:	Die Cast Aluminium
Box Qty:	1 Pcs



Streetlight-High Lumen

100W VT-15105ST

SKU: 5501 - 3000K Warm White 3800157634595



Sensor Compatible:	Yes
Voltage/Frequency:	AC:100-240V,50/60Hz
Luminous Flux:	12400lm
LED Type:	SMD
IP Rating:	IP65
Dimension:	566x268x62mm

CRI:	>70
PF:	>0.90
Beam Angle:	100°
Body Type:	Die Cast Aluminium
Box Qty:	1 Pcs




ADAPTERS FOR STREET LIGHTS



Adapter
VT-795

Box Qty.
10 Pcs

SKU: 3624 3800157608152




Compatible with 100W,120W and 150W models, this adapter allows the angle of the streetlight to be adjusted as per client's requirements.



Adapter
VT-795-1

Box Qty.
12 Pcs

SKU: 3668 3800157625029



Compatible with 30W and 50W models, this adapter allows the angle of the streetlight to be adjusted as per client's requirements.

